

MACHINES AND ACCESSORIES - pneumatic accessories

EWO hand tyre inflators

			
AIRMASTER PREMIUM			
pic.	code	connector	description
1	EW-356221	lever	Hand-held tyre inflator designed for inflating tyres with air and nitrogen. It is equipped with 63 mm pressure gauge (accuracy class 1.0) in a rubber protection cover with double scale (bar, psi). Calibrated - recalibration required every 2 years (Directive 86/217/EEC). A full range of accessories and spare parts is available (see: Hand tyre inflators - accessories). Material: aluminium. Connection: EUROSTANDARD 7.2 plug. Working press.: up to 10 bar. Max. working press.: 12 bar. Working temp.: from -10°C up to +60°C.
2	EW-356223	clip	
3	EW-356222	double-sided push-on	

			
AIRSTAR			
pic.	code	connector	description
1	EW-245201	lever	Hand-held tyre inflator designed for inflating tyres with air and nitrogen. It is equipped with 80 mm pressure gauge (accuracy class 1.0) in a polyethylene protection cover with double scale (bar, psi). A calibrated version requires recalibration every 2 years (Directive 86/217/EEC). A full range of accessories and spare parts is available (see: Hand tyre inflators - accessories). Material: rubber-coated aluminium. Connection: EUROSTANDARD 7.2 plug. Working press.: up to 12 bar. Max. working press.: 12 bar. Working temp.: from -10°C up to +60°C. * without calibration.
2	EW-245261	clip	
3	EW-245211	double-sided push-on	
1	EW-245241*	lever	
2	EW-245271*	clip	
3	EW-245251*	double-sided push-on	