


INDUSTRIAL FITTINGS - quick release couplings

RECTUS couplings



Plug with female thread 	code	thread size	SW [mm]	L [mm]	L1 [mm]	L2 [mm]
	straight through					
	RE-26SFIW10MXX	1/8"	14	30	20	7
	RE-26SFIW13MXX	1/4"	17	33	20	10
	RE-26SFIW17MXX	3/8"	19	33	20	10
	RE-26SFIW21MXX	1/2"	24	38	20	12

Plug with hose tail 	code	hose I.D. [mm]	SW [mm]	L [mm]	D [mm]	L1 [mm]	L2 [mm]
	straight through						
	RE-26SFTF04MXX	4	-	48	12	20	25
	RE-26SFTF06MXX	6	-	48	12	20	25
	RE-26SFTF08MXX	8	-	48	12	20	25
	RE-26SFTF09MXX	9	-	48	12	20	25
	RE-26SFTF10MXX	10	-	48	12	20	25
	RE-26SFTF13MXX	13	-	48	15	20	25

Plug for plastic hose 	code	hose I.D. x O.D. [mm]	SW [mm]	L [mm]	L1 [mm]	L2 [mm]
	straight through					
	RE-26SFKO06MXX	4x6	-	34	20	13
	RE-26SFKO08MXX	6x8	-	34	20	15
	RE-26SFKO10MXX	8x10	17	42	20	17
	RE-26SFKO12MXX	9x12	17	42	20	17

Plug for plastic hose with spring guard 	code	hose I.D. x O.D. [mm]	SW [mm]	L [mm]	L1 [mm]	L2 [mm]
	straight through					
	RE-26SFKK06MXX	4x6	-	120	20	13
	RE-26SFKK08MXX	6x8	-	127	20	13
	RE-26SFKK10MXX	8x10	17	135	20	17
	RE-26SFKK12MXX	9x12	17	142	20	17

Plug with recoil eliminator and hose tail 	code	hose I.D. [mm]	SW [mm]	L [mm]	L1 [mm]	L2 [mm]
	RE-26SRTF06MXX	6	21	67	20	25
	RE-26SRTF08MXX	8	21	67	20	25
	RE-26SRTF09MXX	9	21	67	20	25
	RE-26SRTF10MXX	10	21	67	20	25
	RE-26SRTF13MXX	13	21	67	20	25

Attention!

- steel plugs - see type 25
- plugs with valves for double shut-off version - see type 25