




Fittings for PTFE brake hoses DN3 - reusable

description	code	material	thread size	thread size	L [mm]	L1 [mm]	L2 [mm]	L3 [mm]	CH 1 [mm]	CH 2 [mm]
Male thread. female cone seal 	RK-MACR-0N	chromium plated steel	M10x1.25	-	11	32	-	-	14	11
	RK-MACR-1N		M10x1	-	11	32	-	-	14	11
	RK-MACR-2N		3/8”-24	-	11	32	-	-	14	11
Male thread. male cone seal 	RK-MALR-0N	chromium plated steel	M10x1.25	-	23	45	-	-	14	11
	RK-MALR-1N		M10x1	-	23	45	-	-	14	11
	RK-MALR-2N		3/8”-24	-	23	45	-	-	14	11
Male / female thread 	RK-MFALR-0N	chromium plated steel	M16x1.5	M10x1.25	12	8	37	-	17	11
	RK-MFALR-1N		M16x1.5	M10x1	12	8	37	-	17	11
	RK-MFALR-2N		M16x1.5	3/8”-24	12	8	37	-	17	11
Female thread 	RK-FACR-0N	chromium plated steel		M10x1.25	8	32	-	-	13	11
	RK-FACR-1N			M10x1	8	32	-	-	14	11
	RK-FACR-2N			3/8”-24	8	32	-	-	13	11
Female thread 	RK-FALR-0N	chromium plated steel		M10x1.25	8	37	-	-	17	11
	RK-FALR-1N			M10x1	8	37	-	-	17	11
	RK-FALR-2N			3/8”-24	8	37	-	-	17	11